



**50% of a good balancing depends on the wheel clamping and centring system. Why risk it?**



# FASTPLATE

Wheel balancers



High-precision flange  
for optimal wheel clamping



# FASTPLATE

## MAIN FEATURES

- **Excellent** balancing results!
- **Uniform axle load** distribution, like wheel bolts on the vehicle
- **Quick and easy set-up**
- **Indestructible** and **lightweight (only 1.5 kg)**
- **Secure clamping and balancing.** No damage to alloy wheel surfaces or cracks in plastic-coated wheels
- **Pin heads** that correctly fit steel and alloy rims, **interchangeable** by means of a quick-release system
- **UNIVERSAL.** Applicable to any Mondolfo Ferro  $\varnothing$  40 mm. wheel balancer.

**Competent and fast service will inspire confidence, ensuring greater customer loyalty.**

## PRODUCT OVERVIEW




### 8-21100294 FPF FASTPLATE 5

for 5-hole rims.  
Clamping range  
95.25 - 180 mm



### 8-21100295 FPF FASTPLATE 3-4-6-8

for 3- 4- 6- 8-hole rims.  
Clamping range  
95.25 - 180 mm



### 8-21100296 FPF FASTPLATE KIT

for 3- 4- 5- 6- 8-hole  
rims.  
Clamping range  
95.25 - 180 mm



### 8-21100297 FPF-C SLEEVE HANDLE

Sleeve for automatic  
clamping wheel  
balancers. It screws  
directly onto the  
FASTPLATE to make  
work easier and  
faster

The manufacturer reserves the right to modify the features of its products at any time.