

# C-LINE

# TITAN

XC 3200 EF - XC 3600 EF



**Electrohydraulic underbody double scissors type lift, for tyre specialists, car workshops, and body repairers.**



## Description



**Electrohydraulic underbody double scissors type lift**, for tyre specialists, car workshops, and body repairers.

Alignment of the runways with a dual **MASTER/SLAVE** circuit (**two cylinders per runboard**) without mechanical safety racks.

Runboards version with flaps (**F**).

**All models available in both on-floor and flush installation versions.**

Adjustment bolts with rubber to cushion the end of the stroke



**Runways with suspended flaps** which also act as vehicle access ramps.



**Generously sized, self-lubricating** sliding blocks.



Special **lift linkage**, for lifting loads even from the lowest lift height.



**Unique arm geometry** for maximum stiffness and minimised space usage.

## Technical data

Model	Lift capacity	Lifting time	Three phase motor	Single phase motor	Max. lifting height	Lift min. height
<b>TITAN XC 3200 EF</b>	3200 kg	45 s	230/400V - 3kW	230V - 3kW	1890 mm	105 mm
<b>TITAN XC 3600 EF</b>	3600 kg		3Ph - 50/60Hz	1Ph - 50/60Hz		110 mm

## Supplied accessories

- Self-lubricating bushings on all rotating parts
- Set of 4 rubber pads

## Optional

- Pair of cross pieces and pads for off-road vehicles.
- Kit for pit installations.

## Dimensions

**TITAN XC 3600 EF / TITAN XC 3200 EF**

